

Blocks



PO

MT

6"x30" R - 12"x24" - 18"x18" - Porcelain



Blocks

Technical characteristics report

6"x30" rectified - 12"x24" - 18"x18" - **Porcelain**



JUTA



TOBACCO



DUST



SMOKE

Packing	Pieces/box	M ² /box	Kg/box
6"x30" rectified	7	0.7875	17.50
12"x24"	6	1.0800	23.40
18"x18"	5	1.0125	20.60

Icons		
	Floor tile	<input type="checkbox"/>
	Porcelain	<input type="checkbox"/>
	Matt	<input type="checkbox"/>

Technical characteristics	Tested performed	Required standards	Results
Thickness	-	-	6"x30" rectified: 10 mm 12"x24" - 18"x18": 9,5 mm.
Sizes	UNI-EN ISO 10545-2	<ul style="list-style-type: none"> • Length and width ± 0,6 % max • Thickness ± 5 % max • Linearity ± 0,5 % max • Wedging ± 0,6 % max • Warpage ± 0,5 % max 	According
Water absorption capacity	UNI-EN ISO 10545-3	≤ 0,5%	0.2%
Flexion resistance n/mm ²	UNI-EN ISO 10545-4	≥ 35 N/mm ²	According
Frost resistance	UNI-EN ISO 10545-12	Resistant	Frost-proof
Resistance to álcalis and acids	UNI-EN ISO 10545-13	It stands the test	Resistant
Deep abrasion resistance	UNI-EN ISO 10545-6	≤ 175 mm ³	According
Measurement of coefficient of static friction	ASTM C 1028	U ≥ 0,6	Dry 0.86 - Wet 0.63



www.refin-ceramic-tiles.com

Distributed by:



Pan American Ceramics

16610 Gale Ave. - Industry, CA 91745
Tel. (626) 961-0051 - Fax (626) 336-2217